



Pitch:5.0/5.08mm

MODEL:JL2EDGKBM-5.0/5.08

认证/CERTIFICATION



材质及电镀

| | |
|----|---------------|
| 螺丝 | M3.0, 钢, 镀锌 |
| 夹片 | 磷青铜, 镀镍 |
| 方块 | 黄铜, 镀镍 |
| 塑件 | PA66, UL94V-0 |

电气性能

| | | |
|------|--------------|--------------------|
| 参考标准 | UL | IEC |
| 额定电压 | 300V | 450V |
| 额定电流 | 15A | 20A |
| 使用线径 | 28~14AWG | 2.5mm ² |
| 接触电阻 | 20mΩ | |
| 绝缘电阻 | 500MΩ/DC500V | |
| 耐电压 | AC2000V/1Min | |

机械性能

| | | |
|------|---------------------------|--|
| 温度范围 | -40°C~+105°C | |
| 瞬时温度 | +250°C 5秒 | |
| 扭矩 | 5.10kgf-cm/0.5Nm/4.43Lbin | |
| 剥线长度 | 7~8mm | |

MATERIAL

| | |
|---------|----------------------------|
| Screws | M3.0 Steel Zn plated |
| Clamp | Phosphor bronze, Ni plated |
| Cage | Brass, Ni plated |
| Housing | PA66, UL94V-0 |

ELECTRICAL

| | | |
|-----------------------|--------------|--------------------|
| Standard | UL | IEC |
| Rated voltage | 300V | 450V |
| Rated current | 15A | 20A |
| Wire range | 28~14AWG | 2.5mm ² |
| Contact resistance | 20mΩ | |
| Insulation resistance | 500MΩ/DC500V | |
| Withstanding voltage | AC2000V/1Min | |

MECHANICAL

| | | |
|----------------|---------------------------|--|
| Temp. range | -40°C~+105°C | |
| Max. soldering | +250°C for 5 Sec | |
| Torque | 5.10kgf-cm/0.5Nm/4.43Lbin | |
| Strip length | 7~8mm | |

