



Pitch:5.0/5.08mm

MODEL:JL2EDGKC

认证/CERTIFICATION



材质及电镀

螺丝 M2.0, 钢, 镀锌
 夹片 磷青铜, 镀镍
 方块 黄铜, 镀镍
 滑块 碳钢, 镀锌
 塑件 PA66, UL94V-0

电气性能

参考标准	UL	IEC
额定电压	300V	450V
额定电流	15A	20A
使用线径	28~14AWG	2.5mm ²
接触电阻	20mΩ	
绝缘电阻	500MΩ/DC500V	
耐电压	AC2000V/1Min	

机械性能

温度范围 -40°C~+105°C
 瞬时温度 +250°C 5秒
 扭矩 5.1kgf-cm/0.5Nm/4.43Lbin
 剥线长度 7~8mm

MATERIAL

Screws M2.0 Steel Zn plated
 Clamp Phosphor bronze, Ni plated
 Cage Brass, Ni plated
 Slide block Steel Zn plated
 Housing PA66, UL94V-0

ELECTRICAL

Standard	UL	IEC
Rated voltage	300V	450V
Rated current	15A	20A
Wire range	28~14AWG	2.5mm ²
Contact resistance	20mΩ	
Insulation resistance	500MΩ/DC500V	
Withstanding voltage	AC2000V/1Min	

MECHANICAL

Temp. range -40°C~+105°C
 Max. soldering +250°C for 5 Sec
 Torque 5.1kgf-cm/0.5Nm/4.43Lbin
 Strip length 7~8mm

