



Pitch:5.0/5.08mm

MODEL:JL2EDGKLM

认证/CERTIFICATION	
------------------	--

材质及电镀	
螺丝	M3.0, 钢, 镀锌
夹片	磷青铜, 镀镍
方块	黄铜, 镀镍
塑件	PA66, UL94V-0
电气性能	
参考标准	UL IEC
额定电压	300V 450V
额定电流	15A 20A
使用线径	28~14AWG 2.5mm ²
接触电阻	20mΩ
绝缘电阻	500MΩ/DC500V
耐电压	AC2000V/1Min
机械性能	
温度范围	-40℃~+105℃
瞬时温度	+250℃ 5秒
扭矩	5.10kgf-cm/0.5Nm/4.43Lbin
剥线长度	7-8mm

MATERIAL	
Screws	M3.0 Steel Zn plated
Clamp	Phosphor bronze, Ni plated
Cage	Brass, Ni plated
Housing	PA66, UL94V-0
ELECTRICAL	
Standard	UL IEC
Rated voltage	300V 450V
Rated current	15A 20A
Wire range	28~14AWG 2.5mm ²
Contact resistance	20mΩ
Insulation resistance	500MΩ/DC500V
Withstanding voltage	AC2000V/1Min
MECHANICAL	
Temp. range	-40℃~+105℃
Max. soldering	+250℃ for 5 Sec
Torque	5.10kgf-cm/0.5Nm/4.43Lbin
Strip length	7~8mm

