



Pitch:5.0/5.08mm

MODEL:JL2CDGM

认证/CERTIFICATION

材质及电镀

| | |
|----|---------------|
| 螺母 | M2.5,黄铜 |
| 焊针 | 黄铜, 镀锡 |
| 塑件 | PA66, UL94V-0 |

电气性能

| | | |
|------|--------------|------|
| 参考标准 | UL | IEC |
| 额定电压 | 300V | 450V |
| 额定电流 | 15A | 20A |
| 接触电阻 | 20mΩ | |
| 绝缘电阻 | 500MΩ/DC500V | |
| 耐电压 | AC2000V/1Min | |

机械性能

| | |
|------|--------------|
| 温度范围 | -40°C~+105°C |
| 瞬时温度 | +250°C 5秒 |

MATERIAL

| | |
|------------|------------------|
| Nut | M2.5,Brass |
| Pin header | Brass, Si plated |
| Housing | PA66, UL94V-0 |

ELECTRICAL

| | | |
|-----------------------|--------------|------|
| Standard | UL | IEC |
| Rated voltage | 300V | 450V |
| Rated current | 15A | 20A |
| Contact resistance | 20mΩ | |
| Insulation resistance | 500MΩ/DC500V | |
| Withstanding voltage | AC2000V/1Min | |

MECHANICAL

| | |
|----------------|------------------|
| Temp. range | -40°C~+105°C |
| Max. soldering | +250°C for 5 Sec |

