



Pitch:3.96mm

## MODEL:HT396K

### 认证/CERTIFICATION

### 材质及电镀

螺丝	M2.0, 钢, 镀锌
夹片	黄铜, 镀镍
弹片	黄铜, 镀镍
塑件	PA66, UL94V-0

### 电气性能

参考标准	UL	IEC
额定电压	300V	250V
额定电流	8A	15A
使用线径	26~16AWG	1.5mm <sup>2</sup>
接触电阻	20mΩ	
绝缘电阻	500MΩ/DC500V	
耐电压	AC2000V/1Min	

### 机械性能

温度范围	-40°C~+105°C	
瞬时温度	+250°C 5秒	
扭矩	2.04kgf-cm/0.2Nm/1.77Lbin	
剥线长度	6~7mm	

### MATERIAL

Screws	M2.0 Steel Zn plated
Clamp	Brass, Ni plated
Shrapnel	Brass, Ni plated
Housing	PA66, UL94V-0

### ELECTRICAL

Standard	UL	IEC
Rated voltage	300V	250V
Rated current	8A	15A
Wire range	26~16AWG	1.5mm <sup>2</sup>
Contact resistance	20mΩ	
Insulation resistance	500MΩ/DC500V	
Withstanding voltage	AC2000V/1Min	

### MECHANICAL

Temp. range	-40°C~+105°C	
Max. soldering	+250°C for 5 Sec	
Torque	2.04kgf-cm/0.2Nm/1.77Lbin	
Strip length	6~7mm	

