



Pitch:10.0mm

MODEL:JL501

认证/CERTIFICATION

材质及电镀

螺丝	M3.0, 钢, 镀锌
弹片	磷青铜, 镀镍
方块	黄铜, 镀镍
塑件	PA66, UL94V-0

电气性能

参考标准	UL	IEC
额定电压	300V	250V
额定电流	6.3A	6.3A
使用线径	18-14AWG	2.5mm ²
接触电阻	20mΩ	
绝缘电阻	500MΩ/DC500V	
耐电压	AC2000V/1Min	

机械性能

温度范围	-40°C~+105°C	
扭矩	5.10kgf-cm/0.5Nm/4.43Lbin	
剥线长度	5-6mm	

MATERIAL

Screws	M3.0 Steel Zn plated
Shrapnel	Phosphor bronze, Ni plated
Clamp	Brass, Ni plated
Housing	PA66, UL94V-0

ELECTRICAL

Standard	UL	IEC
Rated voltage	300V	250V
Rated current	6.3A	6.3A
Wire range	18-14AWG	2.5mm ²
Contact resistance	20mΩ	
Insulation resistance	500MΩ/DC500V	
Withstanding voltage	AC2000V/1Min	

MECHANICAL

Temp. range	-40°C~+105°C	
Torque	5.10kgf-cm/0.5Nm/4.43Lbin	
Strip length	5-6mm	

