




Pitch:8.25mm

## MODEL:JL36A

### 认证/CERTIFICATION



### 材质及电镀

|    |               |
|----|---------------|
| 螺丝 | M3.0, 钢 镀镍    |
| 焊脚 | 黄铜, 镀锡        |
| 塑件 | PA66, UL94V-0 |

### 电气性能

|      |              |                    |
|------|--------------|--------------------|
| 参考标准 | UL           | IEC                |
| 额定电压 | 300V         | 450V               |
| 额定电流 | 20A          | 24A                |
| 使用线径 | 22-12AWG     | 4.0mm <sup>2</sup> |
| 接触电阻 | 20mΩ         |                    |
| 绝缘电阻 | 500MΩ/DC500V |                    |
| 耐电压  | AC2000V/1Min |                    |

### 机械性能

|      |                          |
|------|--------------------------|
| 温度范围 | -40°C~+105°C             |
| 扭矩   | 5.1kgf-cm/0.5Nm/4.43Lbin |

### MATERIAL

|            |                      |
|------------|----------------------|
| Screws     | M3.0 Steel Ni plated |
| Pin Herder | Brass, Sn plated     |
| Housing    | PA66, UL94V-0        |

### ELECTRICAL

|                       |              |                    |
|-----------------------|--------------|--------------------|
| Standard              | UL           | IEC                |
| Rated voltage         | 300V         | 450V               |
| Rated current         | 20A          | 24A                |
| Wire range            | 22-12AWG     | 4.0mm <sup>2</sup> |
| Contact Resistance    | 20mΩ         |                    |
| Insulation resistance | 500MΩ/DC500V |                    |
| Withstanding voltage  | AC2000V/1Min |                    |

### MECHANICAL

|             |                          |
|-------------|--------------------------|
| Temp. range | -40°C~+105°C             |
| Torque      | 5.1kgf-cm/0.5Nm/4.43Lbin |

