



Pitch:9.5mm

## MODEL:JL46A

### 认证/CERTIFICATION



### 材质及电镀

螺丝	M4.0, 钢 镀镍
焊脚	黄铜, 镀锡
塑件	PA66, UL94V-0

### 电气性能

参考标准	UL	IEC
额定电压	300V	750V
额定电流	20A	32A
使用线径	22-12AWG	4.0mm <sup>2</sup>
接触电阻	20mΩ	
绝缘电阻	500MΩ/DC500V	
耐电压	AC2000V/1Min	

### 机械性能

温度范围	-40°C~+105°C
扭矩	12.24kgf-cm/1.2Nm/10.6Lbin

### MATERIAL

Screws	M4.0 Steel Ni plated
Pin Herder	Brass, Sn plated
Housing	PA66, UL94V-0

### ELECTRICAL

Standard	UL	IEC
Rated voltage	300V	750V
Rated current	20A	32A
Wire range	22-12AWG	4.0mm <sup>2</sup>
Contact Resistance	20mΩ	
Insulation resistance	500MΩ/DC500V	
Withstanding voltage	AC2000V/1Min	

### MECHANICAL

Temp. range	-40°C~+105°C
Torque	12.24kgf-cm/1.2Nm/10.6Lbin

