



Pitch:7.62mm

MODEL:JL7620B

认证/CERTIFICATION



材质及电镀

| | |
|----|---------------|
| 螺丝 | M3.0, 钢 镀镍 |
| 焊脚 | 黄铜, 镀锡 |
| 塑件 | PA66, UL94V-0 |

电气性能

| | | |
|------|--------------|--------------------|
| 参考标准 | UL | IEC |
| 额定电压 | 300V | 450V |
| 额定电流 | 10A | 17.5A |
| 使用线径 | 22-16AWG | 1.5mm ² |
| 接触电阻 | 20mΩ | |
| 绝缘电阻 | 500MΩ/DC500V | |
| 耐电压 | AC2000V/1Min | |

机械性能

| | |
|------|---------------------------|
| 温度范围 | -40°C~+105°C |
| 扭矩 | 5.10kgf-cm/0.5Nm/4.43Lbin |

MATERIAL

| | |
|------------|----------------------|
| Screws | M3.0 Steel Ni plated |
| Pin Herder | Brass, Sn plated |
| Housing | PA66, UL94V-0 |

ELECTRICAL

| | | |
|-----------------------|--------------|--------------------|
| Standard | UL | IEC |
| Rated voltage | 300V | 450V |
| Rated current | 10A | 17.5A |
| Wire range | 22-16AWG | 1.5mm ² |
| Contact Resistance | 20mΩ | |
| Insulation resistance | 500MΩ/DC500V | |
| Withstanding voltage | AC2000V/1Min | |

MECHANICAL

| | |
|-------------|---------------------------|
| Temp. range | -40°C~+105°C |
| Torque | 5.10kgf-cm/0.5Nm/4.43Lbin |

