



Pitch: 11.5mm

## MODEL: JL-3

认证/CERTIFICATION



### 材质及电镀

螺丝 M4.0, 钢 镀镍  
 焊脚 黄铜, 镀锡  
 塑件 PA66, UL94V-0

### 电气性能

参考标准	UL	IEC
额定电压	300V	450V
额定电流	30A	35A
使用线径	22-10AWG	6.0mm <sup>2</sup>
接触电阻	20mΩ	
绝缘电阻	500MΩ/DC500V	
耐电压	AC2000V/1Min	

### 机械性能

温度范围 -40°C~+105°C  
 扭矩 12.24kgf-cm/1.2Nm/10.6Lbin

### MATERIAL

Screws M4.0 Steel Ni plated  
 Pin Herder Brass, Sn plated  
 Housing PA66, UL94V-0

### ELECTRICAL

Standard	UL	IEC
Rated voltage	300V	450V
Rated current	30A	35A
Wire range	22-10AWG	6.0mm <sup>2</sup>
Contact Resistance	20mΩ	
Insulation resistance	500MΩ/DC500V	
Withstanding voltage	AC2000V/1Min	

### MECHANICAL

Temp. range -40°C~+105°C  
 Torque 12.24kgf-cm/1.2Nm/4.0Lbin

